### UNCLASSIFIED

### AD NUMBER

### AD371793

### **CLASSIFICATION CHANGES**

TO: unclassified

FROM: confidential

### LIMITATION CHANGES

### TO:

Approved for public release, distribution unlimited

#### FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; DEC 1965. Other requests shall be referred to Air Force Rocket Propulsion Laboratory, Attn: Research and Technology Division, Edwards AFB, CA.

### **AUTHORITY**

31 Dec 1977, per document marking, DoDD 5200.10; AFRPL ltr, 7 May 1973

## SECURITY MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

AFRPL-TR-65-232

# (U) MASS SPECTROMETRY OF CORROSIVE OXIDIZERS AND XENON COMPOUNDS

TECHNICAL REPORT AFRPL-TR-65-232

BERGE B. GOSHGARIAN

DECEMBER 1965



AIR FORCE ROCKET PROPULSION LABORATORY
RESEARCH AND TECHOLOGY DIVISION
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
EDWARDS, CALIFORNIA

DOWNGRADED AT 3 YEAR INTERVALS; DECLASSIFIED AFTER 12 YEARS. DOD DIR 5200.10

### CONFIDENTIAL

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws. Title 18, U.S.C., Section 793 and 794, the transmission of which in any manner to an unauthorized person is prohibited by law

#### NOTICES

When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified requesters may obtain copies of this report from DDC. Orders will be expedited if placed through the librarian or other person designated to request documents from DDC.

Do not return this copy. When not needed, destroy in accordance with pertinent security regulations.

AFRPL-TR-65-232

(U) MASS SPECTROMETRY OF CORROSIVE
OXIDIZERS AND XENON COMPOUNDS

TECHNICAL REPORT AFRPL-TR-65-232

BERGE B. GOSHGARIAN

DECEMBER 1965

AIR FORCE ROCKET PROPULSION LABORATORY
RESEARCH AND TECHNOLOGY DIVISION
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
EDWARDS, CALIFORNIA

DOWNGRADED AT 3 YEAR INTERVALS; DECLASSIFIED AFTER 12 YEARS. DOD DIR 5200.10

### CONFIDENTIAL

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws. Title 18, U.S.C., Section 793 and 794, the transmission of which in any manner to an unauthorized person is prohibited by law.

#### **FOREWORD**

This report covers study conducted under Project 314802, Task 314802802, corrosive gas analysis phase. The research was conducted from May 1965 to July 1965.

The task was conducted by the Propellant Division, Chemical Branch, Air Force Rocket Propulsion Laboratory, Edwards, California.

This report has been reviewed and approved.

FI WOOD M. DOUTHETT

Colonel, USAF

Commander, Air Force Rocket Propulsion Laboratory

### (U) ABSTRACT

A mass spectrometric study of reactive and corrosive oxidizers was successfully accomplished using a double-focusing mass spectrometer with a monel-Teflon sample introduction manifold. Reproducible spectra for compound "A", bromine pentafluoride, iodine pentafluoride, xenon tetrafluoride, xenon hexafluoride, oxygen difluoride, and fluorine were obtained with little difficulty after passivation of the manifold. Reaction products of the rhenium filament with oxygen difluoride, the passivation procedure, and the spectra of corrosive gases studied are discussed.

### TABLE OF CONTENTS

Section

Page

1.	INTRODUCTION	1
2.	EXPERIMENTAL PROCEDURES	1
3.	RESULTS AND DISCUSSION	4
4.	CONCLUSIONS	14
	REFERENCES	15
	DISTRIBUTION LIST	
	FORM 1473	
	LIST OF FIGURES	
Figure No.	Title	Page
		Page 3
No.	Title	
No.	Title Corrosive Gas Mass Spectrometer Manifold	3
No. 1 2	Title  Corrosive Gas Mass Spectrometer Manifold  Rhenium Filament Reaction Products (RE + OF <sub>2</sub> )	3
No. 1 2 3	Title  Corrosive Gas Mass Spectrometer Manifold  Rhenium Filament Reaction Products (RE + OF <sub>2</sub> )  Chlorine Pentafluoride (30µa 50 ev)	3 6 8
No. 1 2 3 4	Title  Corrosive Gas Mass Spectrometer Manifold	3 6 8 9
No. 1 2 3 4 5	Title  Corrosive Gas Mass Spectrometer Manifold	3 6 8 9
No. 1 2 3 4 5 6 7	Title  Corrosive Gas Mass Spectrometer Manifold	3 6 8 9 10
No. 1 2 3 4 5	Title  Corrosive Gas Mass Spectrometer Manifold	3 6 8 9 10

### (U) MASS SPECTROMETRY OF CORROSIVE OXIDIZERS AND XENON COMPOUNDS


#### 1. INTRODUCTION.

- (U) The identification of corrosive gas compounds and of impurities in these compounds requires special analytical procedures. The use of a mass spectrometer is particularly desirable since the molecular weight of (as well as the impurities in) the corrosive gas compounds can be obtained. Special handling systems have to be built to introduce these corrosive gases to the mass spectrometer ion source.
- (U) Monel and nickel are the best readily available materials for corrosive gas handling manifolds due to their ability to form tenacious passive coatings with fluorinated gases, and further non-reactivity. Teflon is useful for gasketing and valve seats because of its non-reactivity with low pressure halogens. The elimination of any glass in the introduction manifold is desirable to avoid the formation of silicon tetrafluoride from reaction of fluorinated gases with silicon dioxide.
- (U) This study was undertaken to demonstrate the capability of a double-focusing high resolution mass spectrometer equipped with a monel-Thom introduction manifold for the analysis of corrosive compounds, and to eliminate the probable modes of molecular decomposition of these compounds upon electron impact.

#### 2. EXPERIMENTAL PROCEDURES.

(U) A Mattauch-Herzog type dougle-focusing mass spectrometer manufactured by Consolidated Electrodynamics Corporation was used in this study. Ions produced from sample gas molecule bombardment by 50-volt electrons were accelerated through 8 kv and double-focused by tandem electric and magnetic fields.

- (U) Scanning of the spectrum w. accomplished by varying the magnetic field strength, and detection of the ions was done with a 17-stage electron multiplier. An ion signal of approximately 5 x 10-13 amps at the beam monitor, which collected approximately one-fourth of the ion beam, was maintained throughout a scan. A minimum of five spectra per sample was obtained, and the average of peak height intensities was taken for the patterns presented.
- (U) Pressures in the unheated source were maintained below  $10^{-6}$  torr during scans using a 115 1/sec polyphenylether fluid vapor pump fitted with a liquid nitrogen trap. Even at the average source pressures of  $5 \times 10^{-7}$  torr, and trap current of  $30 \, \mu$  amps, the rhenium filament lasted only 100 hours. Inspection of the burned filament showed that the rhenium had been extensively eroded. All corrosive gas spectra obtained contained lines corresponding to rhenium-oxidizer reaction products.
- (U) The original glass gas introduction system on the instrument was replaced with a monel-Teflon manifold. The valves and connectors were monel, and one valve seat and gaskets were Teflon. The manifold is shown in Figure 1. The  $\frac{1}{4}$ -inch-diameter monel tubing extended to within  $\frac{1}{4}$  inch of the ion source inlet tube, and the connection between the tubes was made with a Teflon tube sleeve. No glass was in contact with the sample gases to preclude the possibility of reactions to form silicon tetrafluoride.
- (U) The monel-Teflon manifold was initially passivated with the corrosive gas under investigation for 12 hours prior to the study. After the passivation procedure, the gas in the manifold was pumped through a charcoal-potassium hydroxide scrubber until the manifold pressure was less than 1 micron. A fresh gas sample was then introduced to 700 torr manifold pressure or sample vapor pressure, and the metering valve regulated so that the ion source pressure did not exceed 1 x 10-6 torr. Spectra were obtained when the source pressure stabilized.
- (U) Fluorine gas at 700 torr was initially used to passivate the manifold. Spectra were obtained 2 hours after the initial fluorine gas introduction. The fluorine was pumped out after 12 hours, and a new



ζ

NOTES

2. HOKE 415A & 3- WAY MONEL-BELLOWS VALVE 1. HOKE MII97 MONEL-TEFLON SEAT BELLOWS VALVE

3. HOKE 413A MONEL BELLOWS VALVE

6. TEFLON TUBE SLEEVE 5. WALLACE & TIERMAN 0-800mm GAUGE

(U) Figure 1 Corrosive Gas Mass Spectronieter Manifold

3

sample of fluorine gas introduced. Spectra of the new sample, after remaining 2 hours in the manifold, were also obtained, and an average of the spectra is compared, in Table I, with that for the initial fluorine passivation.


(C) The chlorine pentafluoride, designated Compound "A", was obtained from Rocketdyne, a Division of North American Aviation, and the bromine pentafluoride and iodine pentafluoride from the Matheson Company. The oxygen difluoride and fluorine were obtained from the Allied Chemical Company, and the xenon tetrafluoride and xenon pentafluoride were prepared at the Air Force Rocket Propulsion Laboratory, using methods described by Chernick (1) and Cady (2).

#### 3. RESULTS AND DISCUSSION.

- (U) The exclusive use of monel and Teflon in the sample introduction manifold proved very satisfactory. Passivation of the manifold with fluorine, and periodic analysis of the gas in the manifold, showed that the fluorine was reacting with either surface contamination or materials within the monel surface. The manifold was thoroughly cleaned and dried prior to fluorine introduction; therefore, it is highly likely that the observed molecular ions in the pre-passivation gas sample, Table I, originated from fluorine reacting with materials on the surface of the monel. Mass spectral analysis of gases in the manifold during passivation can be very useful in determining the completion of the passivation.
- (U) All corrosive gas spectra displayed peaks corresponding to rhenium filament-oxidizer reaction products. The spectrum of oxygen difluoride-rhenium reaction products is shown in Figure 2.
- (U) The  $\operatorname{ReO}_3F^{\dagger}$  ion is the most abundant in the spectrum. Since the +7 oxidation state of rhenium is the most stable, the  $\operatorname{ReO}_3F^{\dagger}$  ion probably originates from the  $\operatorname{ReO}_3F$  parent molecule. The isotope peaks at m/e 268 and 270, are identified as the parent ion  $\operatorname{ReO}_3OF^{\dagger}$  and not  $\operatorname{ReO}_4F^{\dagger}$ . This assignment is made because in  $\operatorname{ReO}_3OF^{\dagger}$  the rhenium is

### CONFIDENTIAL

			TABLE I				
(U)	FLUORINE	PRE- AN	D POST-F	ASSIVAT	ION SPEC	TRA*	
	Ion	Pre- Relative Intensity		Post- Relative Intensity			
<u> </u>	н20	7.94		.04			
	F	.16		.11			
	HF	1.38		. 14			 
	Si, CO, N <sub>2</sub>	1.81		. 08			
	02	.63		. 07			
	F <sub>2</sub>	1.00		1.00			
	CO2	10.9		.03			
<u> </u>	Si F <sub>3</sub>	.81		.02			
		·			ļ		
* ^3m	oles taken	after rema	ining in m	anifold fo	r 2 hours		
<u> </u>							




(U) Figure 2. Rhenium Filament Reaction Products (Re + OF2)

in its stable +7 state, while in order for  $ReO_4F^{\dagger}$  to exist, rhenium would have to exist in an unlikely +9 state.

- (U) One further parent molecular ion,  $\text{ReO}_2\text{F}_2^{+}$ , is observed in the spectrum. This ion peak is small because the rhenium in this molecule must exist in the unstable +6 oxidation state.
- (U) The most probable compounds formed in the reaction of oxygen difluoride with the rhenium filament are, therefore, ReO<sub>3</sub>F, ReO<sub>3</sub>OF, and ReO<sub>2</sub>F<sub>2</sub>.
- (C) The spectra for chlorine pentafluoride, bromine pentafluoride, iodine pentafluoride, xenon tetrafluoride and xenon hexafluoride are shown in Figures 3 to 7.
- (C) As observed, the parent molecular ions for the interhalogens increase in stability as the cation halogen increases in atomic weight. The increasing polarizability of the heavier halogen cations of bromine and iodine and the increased ease of electron removal from the parent molecule by electron bombardment account for this observation.
- (C) The most intense molecule ion in the interhalogen spectra corresponds with the parent molecule minus a fluorine anion. The  $XF_4^+$  ion has an even number of electrons; consequently, it is a stable specie. The  $XF_2^+$  ion likewise has an even number of electrons, and is the second most stable ion, especially in the case of  $ClF_2^+$  and, somewhat, in  $BrF_2^+$ .
- (U) Peaks at mass 158, 160 and 162 in the bromine pentafluoride spectrum were identified as free bromine in the sample. Analysis of the sample by nuclear magnetic resonance spectroscopy also indicated free bromine.
- (C) The ion peaks, HF<sup>+</sup>, Cl<sub>2</sub><sup>+</sup>, and Si F<sub>3</sub><sup>+</sup>, in the chlorine pentafluoride spectra were reproducible and directly related to the chlorine pentafluoride concentration. Since these ions were in negligible concentration after passivation of the manifold, they must be present in the chlorine pentafluoride sample. Infrarea analysis did show hydrogen fluoride and silicon tetrafluoride as impurities in the chlorine pentafluoride.

### CONFIDENTIAL




(C) Figure 3. Chlorine Pentafluoride 30 µa 50 ev

### CONFIDENTIAL

8


This document contains information affecting the national defense of the United States within the meaning of the Espionage Lows, Title 18, U.S.C., Section 793 and 794, the transmission of which in any manner to an unauthorized person is prohibited by law




٤

Ē,

(U) Figure 4. Bromine Pentafluoride (30 $\mu$ a 50 ev)




(U) Figure 5. Iodine Pentafluoride (30 $\mu$ a 50 ev)



ί,

(U) Figure 6. Xenon Tetrafluoride (30µa 50 ev)



(U) Figure 7. Xenon Hexafluoride (30μ a 50 ev)

- (U) The spectra for xenon tetrafluoride and xenon hexafluoride shown in Figures 6 and 7 were at first difficult to obtain. However, little difficulty was encountered after extensive passivation of the manifold with xenon hexafluoride.
- (U) The parent molecular ion  $XeF_4^{\phantom{4}}$  was readily detectable, yet no  $XeF_6^{\phantom{6}}$  ion corresponding to the xenon hexafluoride parent was detected. Studier and Sloth (3) in their mass spectrometric studies also found the  $XeF_4^{\phantom{6}}$  parent ion, but did not detect the  $XeF_6^{\phantom{6}}$  parent ion in normal scans. However, they did detect a small  $XeF_6^{\phantom{6}}$  parent ion during a high-pressure run. The more probable loss of a fluorine anion from xenon hexafluoride rather than from xenon tetrafluoride may be attributed to the weaker bond of the fluorine atom to the xenon in the xenon hexafluoride. Therefore, it is more probable to see the  $XeF_4^{\phantom{6}}$  parent ion than the  $XeF_6^{\phantom{6}}$  parent ion.
- (U) The intense ion peaks  $XeF_5^+$ ,  $XeF_3^+$ , and  $XeF^+$  in the xenon hexafluoride spectrum, again, result from their stable, even electron configuration. The xenon tetrafluoride spectrum does not show the prominent even-numbered electron ion species. Spectra reported by Svec and Flesch (4) show that the even-numbered electron concept does hold for the xenon tetrafluoride cracking pattern. Apparently, our xenon tetrafluoride decomposed at such a rate that the molecular ions observed did not exhibit the true intensity one would obtain from a cracking pattern of unreacted xenon tetrafluoride.
- (U) The ion peaks corresponding to  $Xe^{129}$  isotope and fluorine atoms are larger than the isotopic concentration of  $Xe^{129}$  relative to  $Xe^{132}$ . These ion peaks include ions identified as  $Xe^{132}O^+$ ,  $Xe^{132}OF^+$ ,  $Xe^{132}OF_2^+$ , and originate from  $XeOF_2$  impurity in the sample. The most intense ion specie,  $XeOF^+$ , has a stable, even-numbered configuration.
- (U) The  $Xe^{129}$  isotope and fluorine atom ion peaks in xenon hexafluoride are also larger than the isotopic concentration of  $Xe^{129}$ .

- (U) Ions identified as  $Xe^{132}O^+$ ,  $Xe^{132}OF^+$ ,  $Ye^{132}OF_2^+$ ,  $Xe^{132}OF_3^+$ ,  $Xe^{132}OF_4^+$ , contribute to the  $Xe^{129}F$  series ion peaks. The even-numbered electronic configuration of  $XeOF_3^+$  is again readily observed by its intense peak.
- (U) One would expect to see the parent XeOF type ion species because of the polarizability of xenon, similar to the iodine in the observation of the  ${\rm IF}_5^+$  parent. Since no ion species corresponding to  ${\rm XeOF}_3^+$  or  ${\rm XeOF}_6^+$  were identified, the oxyfluorides in the xenon tetrafluoride and xenon hexafluoride spectra must be  ${\rm XeOF}_2$  and  ${\rm XeOF}_4$ . These oxyfluorides may have originated from reactions of the xenon fluorides with oxygen, water vapor, or silicon dioxide (5).

#### 4. CONCLUSIONS.

- (U) Modification of the mass spectrometer sample inlet manifold to exclude glass and other potentially reactive materials of construction has proven efficacious for the study of corrosive oxidizers. Reproducible spectra of corrosive gases could be recorded after positivation, indicating that the passivation procedure reported is adequate.
- (U) Ion peaks corresponding to impurities like hydrogen fluoride and silicon tetrafluoride in the gases studied were reproducible, showing that this method can be used to identify impurities in corrosive gases with little contribution from products arising from reactions with the mass spectrometer ion source or sample inlet manifold.
- (U) The rhenium filament in the ion source used to produce electrons for ion production must be replaced frequently. Rhenium is presently the only filament material available which shows reasonable non-reactivity toward corrosive gases. Nickel appears promising, but has not been investigated.
- (U) Mass spectrometric studies of reactive gases can be conducted satisfactorily if resistant materials for the sampling manifold are selected and if appropriate passivation procedures are used.

#### REFERENCES

- 1. H.H. Hyman, "Noble Gas Compounds", University of Chicago Press, Chicago, Illinois, p. 36 (1963).
- 2. Ibid., p. 61-63.
- 3. M.H. Studier and E.N. Sloth, <u>Journal of Physical Chemistry</u>, <u>67</u>, 925 (1963).
- 4. H.J. Svec and G.D. Flesch, Science, Vol. 142, 954 (November 1963).
- 5. H. H. Hyman, "Noble Gas Compounds", University of Chicago Press, Chicago, Illinois, 1. 106-108 (1963).

Unclassified
Security Classification

DOCUMENT COL	NTROL DATA - R&	D	
(\$ecurity classification of title, body of abatract and indexis 1. ORIGINATING ACTIVITY (Corporate author)	ng ennotation must be er		
Dept. of the Air Force (AFSC)			onfidential
Research & Technology Division		25 GROUP	
Air Force Rocket Propulsion Lab., E	dwards, Cal.		4
3. REPORT TITLE		<del></del>	
Mass Spectrometry of Corrosive Oxid	izers and Xen	on Com	pounds (U)
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (Leat name, first name, initial)		······································	
Goshgarian, Berge B.			
6. REPORT DATE	7a. TOTAL NO. OF P	AGES	75. NO. OF REFS
December 1965	15		5
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S R	EPORT NUM	BER(S)
ł	_		
b. PROJECT NO. 314802	AFRPL-TR	65-232	
c Task No. 314802802	9 b. OTHER REPORT NO(S) (Any other numbers that may be sasignal this report)		
d.			
10. A VAIL ABILITY/LIMITATION NOTICES	<del> </del>		
Qualified requesters may obtain copie	<del>,</del>	·	
11. SUPPLEMENTARY NOTES	12. SPONSORING MILI	TARY ACT	VITY
	See Blo	ck l	
13. ABSTRACT		· · · · · · · · · · · · · · · · · · ·	
(U) A mass spectrometric study of resuccessfully accomplished using a domonel-Teflon sample introduction macompound "A", bromine pentafluoride xenon hexafluoride, oxygen difluoride difficulty after passivation of the man filament with oxygen difluoride, the porrosive gases studied are discussed.	uble-focusing misold. Repro e, iodine penta , and fluorine ifold. Reaction assivation pro	mass spectation of the second	spectrometer with a spectra for e, xenon tetrafluoride, btained with little acts of the rhenium

DD 15084 1473

Unclassified

Security Classification

#### Unclassified

4.	LIN	KA	LINK B		LINKC	
KEY WORDS	ROLE	₩Ť	ROLE	WT	ROLE	WT
Oxidizer Mass Spectrometry						
Corrosive Oxidizers		l				
Xenon Compounds						
		1				!
			ł [			

#### INSTRUCTIONS

- 1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.
- 2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
- 3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.
- 4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
- 5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. It military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
- 6. REPORT DATE: Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.
- 73 TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.
- 8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, &, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).
- 10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DIYC. Other qualified DDC users shall request through
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

- 11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.
- 12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.
- 13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

Unclassified

Security Classification